

# ENRD LOGO GUIDELINES


## **VERSIONS**

## **FULL VERSION**

The full version is the generic version. It cannot be altered.

#### **FULL COLOURS**

Positive



Negative

#### **GRAYSCALE**

Positive (allowed only on a white background)



## **BLACK AND WHITE**

Positive Negative





## **VERSIONS**

## SHORT VERSION

The short version is allowed only to be used when the full version is present in the same page or screen.

## FULL COLOURS

Positive



Negative



GRAYSCALE

Positive (allowed only on a white background)



BLACK AND WHITE

Positive



Negative



## COLOURS

## COLORS FOR THE ENRD LOGO

	CMYK	Pantone	RGB	Hex
	100	Pantone Reflex Blue	0	#003399
	80		51	
	0		153	
Blue	0			
	40	Pantone 381	177	#b1c800
	0		200	
	100		0	
Light Green	0			
	0	Pantone Yellow	255	#ffdd00
	10		221	
	100		0	
Yellow	0			
	25	Pantone 131	200	#c88910
	50		137	
	100		16	
Ocre	0			
	0	Black	0	#000000
	0		0	
	0		0	
Black	100			
	0	Pantone 423	156	#9c9e9f
	0		158	
	0		159	
Grey	50			

## COMPLEMENTARY COLOR

	CMYK	Pantone	RGB	Hex
	100	Pantone 327	0	#008c8d
	25		140	
	50		141	
Dark Green	0			

## PROTECTION AREA

The protection area is the minimum area around the logo that should remain clear of text and other graphic elements. This makes the logo visible and prevents it getting mixed with other visual elements.

The size of the protection area is based on one star from the ENRD logo.

#### **FULL VERSION**



## SHORT VERSION



## MINIMUM SIZE

To make sure the logo is always clear and legible, there is a minimum size requirement. The minimum size requirement is based on the width of the ENRD logo.

#### **PRINT**

**FULL VERSION** 



Minimum width: 30 mm

#### SHORT VERSION



# DIGITAL

**FULL VERSION** 



Minimum width: 125 pixels at 72 dpi

#### SHORT VERSION

